



## EATON 3105 UPS TECHNICAL SPECS

### → Battery Runtimes

Model Number	PW 3105 500A	PW 3105 700A
Capacity	500VA/300W	700VA/420W
Dimensions (mm)	180x280x115	180x280x115
Unit Weight (kg)	5	6.5
Input Connection	1.8 meter line cord IEC to Australian 10Amp Plug	
Output Connection	6 Australian 10Amp Outlets (3 Battery Backup & Surge Protection, 3 Surge Protection only)	

### Operation

Input Voltage Range	0-300Vac
Output Voltage Range	Nominal -18% to +10%
On Battery Output Voltage	Nominal -12% to +10%
Frequency	50 Hz
Lighting / Surge Protection	476 joules
Safety	AS/NZS62040.1.1, AS/NZS60950, A-Tick
EMI	AS/NZS62040.2, AS/NZSCISPR22, C-Tick
Transfer Time to Battery/AC	2-6 msec. typical
Battery Type	Sealed, maintenance free lead-acid battery
Typical Backup Time	3 minutes at full rated load
Internet / Phone / Fax Protection	RJ11
Short Circuit Protection	Circuit Breaker
Communication Port	USB

### Environmental

Operation Temperature	0°C - 40°C
Operation Relative Humidity	0-95%non condensing
Storage Temperature	-15°C - 50°C

### Software

LanSafe Software is included free of charge.

### Service Plans

Optional Extended Warranty and On Site Changeover service plans available



## EATON 3105 BATTERY RUN TIMES (IN MINUTES)

Model   Load (VA)	80	170	250	330	400	500	600	700
31050500A	43	17	11	6	4	3	-	-
310507000A	53	30	14	9	7	6	4	3

